

UVS

UNIVERSAL VOICE SYSTEM



Honeywell's new Universal Voice System (UVS) helps you increase the value of every sale by adding an entirely new level of comfort and protection to your customers' lives. The Universal Voice Control Module (UVCM) connects quickly and easily to a VISTA control and one standalone intercom station (UVST)—expanding into a powerful indoor/outdoor home communication system*.

Two-way audio verification technology significantly reduces false alarms, and lifestyle-enhancing convenience features including an intercom, baby monitor and speakerphone simplify your customers' lives while providing increased peace of mind. The optional outdoor cover (UVST/ODC) fits over the UVST station for use as an entranceway visitor screening station.

* with the addition of intercom stations (up to seven)

FEATURES

Audio Alarm Verification

- Two-way voice communication with the central station in the event of an alarm

Intercom

- Broadcast a message to all stations in the home
- Hold a private conversation between two stations
- With the outdoor station, answer the front door without opening it to strangers

- With a touchtone phone, the consumer can conduct a two-way voice conversation with someone on the premises

Speakerphone

- Broadcast the ringing of your phone over the stations
- Answer calls from any station
- Transfer a caller to another inside station
- Hands free conversation between stations

- Hands free conversation on incoming phone calls
- Supports call waiting

Audio System

- Any station can become a baby monitor
- Connect to a stereo input for music throughout the home
- Security messages annunciate over the stations with a 4286 VIP Module

UVS

UNIVERSAL VOICE SYSTEM

SPECIFICATIONS

Physical

UVST Dimensions:

- 5-1/8" H x 2-3/4" W x 1-1/2" D

UVCM Dimensions:

- 10" H x 10" W x 3" D

Electrical

UVST Ratings:

- Operating Voltage: 9VDC to 14VDC

- Current Drain: 10mA
idle/70mA active

- Wire Run Length:
 - Home run 22AWG, 4
conductor cable back to
UVCM, 200 feet maximum

- Temperature Range:
 - 14°F to 140°F (-10°C to +60°C)

- Maximum Stations:
 - Supports up to seven stations
total. Up to two stations may be
used outside.

UVCM Ratings

- Operating Voltage: 10VDC
to 14VDC
- Current Drain: 60mA
idle/110mA active

ORDERING

UVS	Universal Voice System (consists of (1) UVCM AND (1) UVST)
UVCM	Control Module
UVST	Universal Voice Station
UVST/ODC	Outdoor Cover
4286	VISTA Interactive Phone Module

Honeywell Security & Custom Electronics

Honeywell International Inc.

PO Box 9035

Syosset, NY 11791

www.honeywell.com

RE06052

L/UVS/D

November 2006

© 2006 Honeywell International Inc.

Honeywell